

TEST REPORT

Client: Massow Interiors Ltd.
471-473 The Arches
Dereham Place
London
EC2A 3HJ

FAO: Barend Massow Hemmes



Sample **AURA WITH SPINNING**

Laboratory No: S1203091/AT/AM1 Reference No: ---

Amendment to report number S1203091/AT dated 9th August 2012.

Order No: --- Date received: 19th June 2012

Description: Class I ordinary fixed or portable luminaire. 60W E27 GLS lamp. Cap-up plastic T190 lamp holder. Pendant or portable luminaire. Lamp holder assembly is covered by a wooden open frame shade. Supplied by household wiring or moulded on 3-pin mains plug fitted with 3A fuse and supply cord fitted with an in-line switch.

Test conducted: Test for compliance with BS EN 60598-1 : 2008 + A11 with reference to EN 60598-2-1 : 1989 (fixed luminaires) and EN 60598-2-4 : 1997 (portable luminaires).

Conclusion The sample **complied** with the European standard.

Martin Langdown
Manager - Electrical Products

2nd November 2012

All results relate only to the sample(s) received for testing.
This report shall not be reproduced except in full, without the written permission of the laboratory.



Sample: **AURA WITH SPINNING**
Laboratory No: **S1203091/AT/AM1**

REPORT DETAILS

BS EN 60598-1 : 2008 + A11

The clause numbers below relate to the sections EN 60598.

The date of testing shall be taken as between the date of the initial receipt of the sample and the date of the issue of the report unless otherwise specified.

Any clauses not mentioned are not applicable.

Responsible technician: Yasin Khan

2	Classification	Pass
3	Marking	Pass
4	Construction	Pass
5	External and internal wiring	Pass
7	Provision for earthing	Pass
8	Protection against electric shock	Pass
9	Resistance to dust and moisture	Pass
10	Insulation resistance and electrical strength	Pass
11	Creepage distances and clearances	Pass
12	Endurance and thermal tests	Pass
13	Resistance to heat	Pass
14	Screw terminals	Pass
15	Screwless terminals	Pass

Clauses 4.4, 4.20, 4.24, 9.2.0 – 9.2.3, 9.2.6 – 9.2.8, 14 & 15 are outside the scope of our UKAS accreditation.

Lamp (bulb) safety is outside the scope of EN60598 and hence this report. If the luminaire is to be sold with a lamp, this should be separately certified.



Sample: **AURA WITH SPINNING**
Laboratory No: S1203091/AT/AM1

CRITICAL COMPONENT LIST:

Component	Manufacturer/ Trademark	Type/Model	Technical Data	Certificate Standard	Certificate Body
Lampholder	ARDITI	A800/C1	T190	EN 60234	IMQ
Supply Cable	HANG ZHOU HONG SHI ELECTRICAL LTD	H03VV-F	3 X 0.75mm ²	HD 21	VDE
Terminal Block	VASK COMPONENTS	T04	450V	EN 60998	VDE
Switch	SCOLMORE	SW3Z02-1	250V 2A	EN 61058	BSI
Mains Plug	SCOLMORE	SW 268	250V 13A	BS 1363	BSI
Mains Fuse	RICHSTAR	--	3A	BS 1362	BSI

Sample: **AURA WITH SPINNING**
 Laboratory No: S1203091/AT/AM1

COMMENTS

N.B. Standard limits are given in brackets, as applicable.

Marking

**The supplier has declared that the following information will be correctly positioned durably and legibly on the luminaire:

The name of manufacturer/supplier, the model, the rated wattage (60W), the rated voltage (240V), the rated frequency (50Hz), the lamp type, type Y cord warning, terminal identification, wiring/installation instructions



Wiring

The supply cable type fitted had a cross-sectional area of 0.75mm² and was of type H03VV-F
 The internal PVC wiring had a basic insulation thickness of 0.5mm and a cross-section of 0.75mm²

Earthing, insulation resistance and electric strength

Earth terminal resistance was measured to be: 0.06Ω [≤ 0.5 Ω]

The insulation resistance at 500V DC between:

Live parts and Class I parts > 100 MΩ [≥ 2 MΩ]

Live parts and accessible Class II parts > 100 MΩ [≥ 4 MΩ]

Live parts of different polarity > 100 MΩ [≥ 2 MΩ]

The electric strength of insulation was tested with an AC voltage between the following:

Live parts and Class I parts: 1.6kV [≥ 1.5 kV]

Live parts and accessible Class II parts 3.2kV [≥ 3 kV]

Live parts of different polarity was tested at: 1.6kV [≥ 1.5 kV]

The leakage current between live and Class I parts was: 0.04mA [≤ 3.5mA]

The leakage current between live and accessible Class II parts was: 0.01mA [≤ 0.7mA]

Heating

Under the normal operating conditions of Clause 12.4, the following temperatures were recorded:

Lamp-cap 151°C [≤ 215 °C]

Lampholder skirt 134°C [≤ 195 °C]

PVC internal wiring (not heat resisting sleeved) 87°C [≤ 95 °C]

PVC internal wiring at bifurcation point 78°C [≤ 95 °C]

Mounting surface 50°C [≤ 95 °C]

Shade 34°C *

* No limit in EN60598 for external surfaces (except of those of handles, knobs and the like). In the current absence of such a limit, for safety it is recommended that they do not exceed 85°C; ref. EN 60335-1 Safety of Electrical Household Appliances.



Sample: **AURA WITH SPINNING**
Laboratory No: S1203091/AT/AM1

ILLUSTRATION


